



## Product Specification Sheet Centerfire Pistol & Revolver

**LOAD NUMBER:** P10T1

**CALIBER:** 10 MM Auto

**CASE:** Nickel Plated Brass (Copper Alloy No. 260)

**BULLET:** 180 Gr. Trophy Bonded Jacketed Soft Point

**PRIMER:** Federal No. 150

Primer Mix contains Basic Lead Styphnate.

Operating Range (-40 degrees to +125 degrees Fahrenheit).

**PRIMER SEALANT:** Water Resistant Anaerobic Sealant

**CASE MOUTH SEALANT:** Water Resistant

**HEADSTAMP:** Each loaded cartridge shall be headstamped with the manufacturer's symbol and appropriate cartridge designation

**ACCURACY:** Three 5-round groups with maximum average extreme spread of 3.0" at 50 yards, using a Mann Rest Test System.

**INSTRUMENTAL VELOCITY:** 1275 +/- 50 FPS using a 5.00" SAAMI standard test barrel

**MUZZLE ENERGY:** 650 Ft-Lbs.

**CHAMBER PRESSURE:** Piezotronic maximum average per 10 rounds -37,500 PSI

**BULLET PULL:** Minimum individual 80 Lbs.

**PROPELLANT DETECTION:** 100% mechanical and/or electrical detection of propellant levels within the cartridge

**VISUAL INSPECTION:** 100% visual inspection of finished cartridges prior to packaging

**LOT IDENTIFICATION:** Each lot of ammunition is assigned a unique identification number to include the day, month and year of manufacture and assembly line on which manufactured

**PACKAGING:** 10-20 Round cartons per 200 round case.